



Quality
makes it a LEER!

INDOOR ICE MERCHANDISERS





Leer Quality... Unequaled in the Industry

All Leer indoor merchandisers feature the finest cabinet construction assembled under the industry's toughest quality-control standards.



model 30



model 40



model 65



The Features that Set the Standard

Leer indoor merchandisers feature triple-pane, tempered safety glass doors; illuminated interior; full top refrigeration cover; quick recovery, low-temp, balanced refrigeration; total steel cabinet construction; and optional custom finishes.

model 60

model 75



model 85



model 100



specifications

| Ice Merchandiser | | | | Outside Dimensions | | | Glass Door | Approx. Wt. ^① | | Refrigeration | Amperage | |
|------------------|--------------|-------------------|---------------|--------------------|---------------------------------|---------|----------------|--------------------------|--------------|---------------------|-----------|---------------------------|
| Models | No. of Doors | Capacity | | Width | Depth ^② ^③ | Height | Width x Height | Cold Wall | Auto Defrost | Compressor 115/1/60 | Cold Wall | Auto Defrost ^④ |
| | | Cu. Ft. (approx.) | Bags* (7 lb.) | | | | | | | | | |
| 30C 30A | 1 | 30 | 80 75 | 36" | 30" | 76-1/2" | 28" x 47" | 330 | 355 | 1/4 hp | 4.7 | 5 |
| 40C 40A | 1 | 40 | 165 160 | 50-1/2" | 30" | 76-1/2" | 28" x 47" | 380 | 405 | 1/3 hp | 6.2 | 6.9 |
| 65C 65A | 1 | 65 | 260 215 | 64" | 35-1/2" | 76-1/2" | 28" x 47" | 455 | 490 | 1/3 hp | 6.2 | 6.9 |
| 60C 60A | 2 | 60 | 265 260 | 73" | 30" | 76-1/2" | 28" x 47" | 530 | 565 | 1/2 hp | 10.2 | 11.6 |
| 75C 75A | 2 | 75 | 290 275 | 73" | 35-1/2" | 76-1/2" | 28" x 47" | 560 | 595 | 1/2 hp | 10.2 | 12 |
| 85C 85A | 2 | 85 | 345 325 | 84" | 35-1/2" | 76-1/2" | 28" x 47" | 610 | 650 | 1/2 hp | 10.2 | 12 |
| 100C 100A | 2 | 100 | 400 380 | 96" | 35-1/2" | 76-1/2" | 28" x 47" | 660 | 695 | 1/2 hp | 10.2 | 12 |

Model Letter Suffixes:

"C" - Cold Wall

or

"A" - Automatic Defrost

① Shipping weight

② Add 3-1/2" for door and handle

③ Add 3" for condensate evaporator

④ Add 1.1 amps for condensate evaporator

standard features

- Total steel cabinet construction
- Baked-on acrylic polyurethane, high solids, lead-free, enamel finish exterior
- Full 2-1/2"-thick, CFC-free, foamed-in-place polyurethane insulation in all walls and top with 3" bottom insulation
- Interior air flow ducts on automatic defrost models
- Triple-pane, tempered safety glass doors with self-closing hinges
- Illuminated interior
- R134a, low temperature, sealed condensing units
- Full top refrigeration cover
- Cold wall or automatic defrost refrigeration systems available on all models
- Condensate evaporator on automatic defrost models
- Five-year compressor warranty
- One-year parts warranty

* Merchandiser storage capacity may vary due to type of ice, ice bag size differences and methods of loading.

options

- Custom painted exterior
- Custom silk screening
- 220/1/50 voltage
- Heavy-duty refrigeration (automatic defrost models only)
- Reverse fan self-cleaning condensing unit

note

- Glass door models are designed for use in stores where temperature and humidity are maintained at 75°F and 55% RH respectively.

Material and product improvement is a constant commitment at Leer Limited Partnership. These specifications are subject to change without notice and without incurring responsibility for previously sold merchandisers and components.



LEER LIMITED PARTNERSHIP

206 Leer Street, Box 206 • New Lisbon, WI 53950-0206
 800-766-5337 • Ph: 608-562-3161 • Fax: 608-562-3203
 Web Site: www.leerlp.com • E-Mail: info@leerlp.com



Printed In The USA
 © LQA D03